

Mosaic™ Programme mechanisms

international standards socket outlets



Selection chart for boxes, supports and plates **p. 838-839**

Pack	Cat.Nos	Other standard socket outlets
10	0 775 01	Euro-US standard - white 1 module
10	0 775 02 ¹	2 modules
10	0 775 03	US standard - white 1 module
10	0 775 04	2 modules - 15 A
10	0 775 05	British standard - white 2 modules - 13 A
10	0 775 10	Italian type - white 1 module - 10 A - screw terminals
10	0 775 11	1 module - 10/16 A - screw terminals
10	0 775 12	German-Italian standard 2 modules - 16 A - screw terminals Not compatible with a 2-module support
10	0 775 06 ¹	Swiss type - white 2 modules - type 13
10	0 775 08 ¹	Danish standard - white 2 modules - with shutters for child protection
10	0 775 09 ¹	2 modules - for UPS - with shutters for child protection
10	0 771 50	2P ELV socket outlet With shutters for child protection For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking 1 module - white antimicrobial
1	0 787 00	Equipotential socket Equalises the voltages of all the conductive elements and all the exposed conductive parts, as well as limiting the contact voltage to a value that is not dangerous for people. For use in hospital environments to prevent disturbance of sensitive equipment Conforms to standards DIN 42801 and IEC 60364-7-710 1 module White antimicrobial
10	7 759 93	Equipotential plug Equipotential connection plug

1: Can be installed in receptacles for floor sockets (p. 389)

Mosaic™ Programme mechanisms

USB charging sockets



Selection chart for supports and plates **p. 838-839**
Technical characteristics, **see e-catalogue**

Pack	Cat.Nos	USB charging sockets
		For recharging portable devices Conform to IEC 62684-2011-01 Consumption in passive mode < 0.1 W 2P+E tap-off connection via 2.5 mm² screw terminals Supplied cordless
5 1	0 775 94 ¹ 0 793 94 ¹	Double USB sockets - 5V- 2400 mA (1500 mA until 1-07-2016) For telephones, smartphones, MP3/MP4 players and fast-charging tablet PC 2 modules ○ White ● Alu
10 1	0 775 91 0 793 91	Single USB sockets - 5V- 750 mA For telephones and smartphones 1 module ○ White ● Alu
1	0 775 96	Micro USB charging dock Cordless micro USB docking station for charging a smartphone 5 V – 2400 mA power supply (1500 mA until 1-07-2016) Screen remains visible during charging Equipped with: - a lateral USB port for an additional device - a smartphone clamp-holder with a non-slip and anti-scratch finish coat Possible to charge an iPhone by using the micro USB Lightning adaptor iPhone is a registered Apple brand The accessory is not supplied with the product ○ White
1	0 775 97	Support for portable device during charging Multigang installation with 2xUSB charger or with a 2P+T and a mobile charger Flat frame does not require a wall shutter box (fix using screws or adhesive on all surface) Prevents device from any risk of falling and allows secure use of device while charging Wall-mounting clamp For 1 portable device ○ White

1: Can be installed in receptacles for floor sockets (p. 389)