


128, av. du Maréchal-de-Lattre-de-Tassigny - 87045 LIMOGES Cedex Tel: 0 (+33) 5 55 06 87 87 - Fax: 0 (+33) 5 55 06 88 88 www.legrand.com




1. USE

For recharging portable devices such as phones, smartphones, tablets, PC, MP3 or MP4 players, loudspeakers, watches, game consoles, powerbanks.

2. RANGE

| Designation | White | Anthracite | Aluminium |
|-----------------------------------|----------|------------|-----------|
| Double USB socket - 5 V - 2400 mA | 0 775 94 | 0 791 94 | 0 793 94 |

3. OVERALL DIMENSIONS (mm)



4. CONNECTION

Type of terminals: with screws Terminal capacity: 2 x 2.5 mm² Stripping length: 6 mm Screwdriver: flat 3.5 mm

Recommended use: circuit terminal outlet

5. TECHNICAL CHARACTERISTICS

5.1 Mechanical characteristics

Impact tests: IK 04 Penetration by solid bodies/liquid: IP 40

■ 5.2 Material characteristics

Base: PC

Cover-plate: PC

Self-extinguishing:

- + 850° C / 30 s for insulating parts holding live parts in place.
- + 650° C / 30 s for other parts made of insulating materials.

5.3 Climatic characteristics

Storage temperature: - 20° C to + 70° C Operating temperature: 0° C to + 45° C

5.4 Electrical characteristics

All values listed below are measured at an ambient temperature of $+ 25^{\circ}$ and after 15 minutes of operation.

| Nominal input voltage | 220 - 240 V~ | |
|---|--------------|--|
| Nominal input frequency | 50-60 Hz | |
| Maximum input current | 300 mA | |
| Maximum power consumption in standby | 0.1W | |
| Power average efficiency | 81 % | |
| Nominal output voltage | 5 V | |
| Maximum output current | 2400 mA | |
| No-load power consumption class and average efficiency level: | | |

No-load power consumption class and average efficiency level: level VI*

| Safety-standard | EN60950-1 |
|------------------|------------------|
| Protection class | ll - Low voltage |

*NB: European Regulation No. 278/2009 of 6 April 2009, Directive 2005/32/EC on eco-design requirements for AC/DC power supplies.

- 5.5 Average charging time for devices equipped with litium ion polymer batteries:
- 80 % charged < 1 h 15
- 100 % charged < 2 h 00

5. TECHNICAL CHARACTERISTICS (continued)

■ 5.6 Charge time for a smartphone with 2400 mA charger plug:

| Manufacturer brand | Smartphone model | Charge time to 100 % |
|--------------------|------------------|----------------------|
| Samsung | Galaxy S6 | 1 h 43 |
| Nokia | Lumia 735 | 2 h 11 |
| Nokia | Lumia 930 | 2 h 11 |
| Google | Nexus 6 | 3 h 02 |
| Google | Nexus 7 | 2 h 58 |

*Data valid as at 1 March 2016.

Note: To optimize the charging time of your device, ensure turn it off during the charging phase.

6. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichlorethylene.

| Caution: A preliminary test should be carried out if specific clean | ning |
|---|------|
| products are to be used. | ÷ |
| ······································ | |

7. STANDARDS AND APPROVALS

IEC 60950-1: low voltage directive.

IEC 62684 / EN 50558 conform to the interoperability specifications of common external power supply (EPS) for use with mobile telephones. Conform to eco design directive 2009/125/EC.