

# OSMOZE

## 8 mm

# ALSAFLOOR



The pleasure of wood veining. Specially designed patterns echoing the charm of yesteryear



### Technical features

|                                              |                             |
|----------------------------------------------|-----------------------------|
| Thickness                                    | 8 mm                        |
| Clip system                                  | 5G                          |
| V-grooves                                    | On the 4 sides              |
| Panel                                        | HDF                         |
| Texture                                      | * In-registered texture     |
| Class of use                                 | 23/33                       |
| Abrasion resistance                          | AC5                         |
| Logistics                                    | Dimensions : 1286 x 192 mm  |
|                                              | 1 kit = 9 planks = 2.22 sqm |
|                                              | sqm/pallet = 106.7 sqm      |
|                                              | 1 pallet = 48 kits          |
|                                              | Kit weight = 16 kg          |
| Pallet weight                                | 768 kg                      |
| Warranty                                     | 25 years                    |
| Number of designs                            | 18                          |
| Fire resistance                              | CFL S1                      |
| Formaldehyde rate                            | E1                          |
| Resistance to chemical agents - EN 438-2-26  | Group 1/2 : 5 - Group 3 : 4 |
| Resistance to cigarettes burns - EN 438-2-18 | Degree 4                    |
| Resistance to light effect EN 438-2-16       | Degree $\geq 6$             |
| Thermal resistance sqm K/W                   | $\leq 0,15$                 |

NEW !



\* A VOC rating expresses the amount of volatile material in the interior air which may present a health hazard when inhaled. It is measured on a scale from A+ (very low emissions) to C (high emissions).

# OSMOZE


## 8 mm

# ALSAFLOOR



420 TAZA OAK\*

Ref : 523123  
Gen : 3512485231239



436 ALPACA  
OAK \*

Ref : 545586  
Gen : 3512485455864



437 GREY  
BUILDING \*

Ref : 545587  
Gen : 3512485455871



448 GREY  
OAK \*

Ref : 523125  
Gen : 3512485231253



449 NEVADA  
OAK \*

Ref : 523126  
Gen : 3512485231260



450 NATURE  
OAK \*

Ref : 523127  
Gen : 3512485231277



514 NAMUR \*

Ref : 545588  
Gen : 3512485455888



518 RAFIA \*

Ref : 523108  
Gen : 3512485231086



528 CHESTNUT  
OAK \*

Ref : 523109  
Gen : 3512485231093



529 ALMOND  
OAK \*

Ref : 523110  
Gen : 3512485231109

\* In-registered texture



# OSMOZE

## 8 mm

# ALSAFLOOR

NEW



535 PRALINE  
OAK \*

Ref : 523111  
Gen : 3512485231116



536 LINEN OAK \*

Ref : 523112  
Gen : 3512485231123



541 COCONUT  
OAK \*

Ref : 538054  
Gen : 3512485380548



542 CHOKEBERRY  
OAK \*

Ref : 538082  
Gen : 3512485380821



559 CARMINE  
OAK \*

Ref : 590120  
Gen : 3512485901200



701 PLATO \*

Ref : 572886  
Gen : 3512485728869



702 ARISTOTLE \*

Ref : 572887  
Gen : 3512485728876



705 PAPYRUS \*

Ref : 572889  
Gen : 3512485728890

\* In-registered texture