

Spyke 24D (gen4)



DRIVETRAIN

Crankset
Surface alloy, 140mm, 32T chainring

Max Chainring Size
32T

Bottom Bracket & Type
BSA68

Shifter(s)
R: Shimano Revoshift SL-RV400-7R, 7-speed Grip Shift

Rear Derailleur
Shimano Tourney RD-TY500, 7-Speed

Cassette
Shimano CS-HG200-7 12-28T, 7-speed

Chain
Shimano CN-HG40, 7-Speed

BRAKES

Brakes
F: Tektro MD-M280 Mechanical Disc
R: Tektro MD-M280 Mechanical Disc

Rotors
F: 160mm, 6-Bolt
R: 160mm, 6-Bolt

€499,00

SPECIFICATIONS.

FRAMESET

Frame
Hydro formed 24" 6061 Aluminium, 1-1/8" Headtube 135mm OLD QR Dropouts, disc brake mounts

Headset
1-1/8" Headset, Press in cups

Frame Axle Spacing
135x9mm

Axle Specification
QR

Hanger Type
HANGER 05

SUSPENSION

Fork
Zoom Steel Suspension fork, 50mm travel, Coil

Fork Travel
50mm

WHEELS

Wheelset
SURFACE Custom Wheelset

Hubs
F: Alloy, 28H, 100 x 9mm QR, 6-bolt
R: Alloy, 28H, 135 x 9mm QR, 6-bolt

Rims
F: 24" Alloy Single Wall, 28H
R: 24" Alloy Single Wall, 28H

Tyres
F: 24 x 2.35" Wanda P1226
R: 24 x 2.35" Wanda P1226

Max Tyre Size
2.35"

COCKPIT

Grips
110mm Long, Grip Shift

Handlebar
Alloy, 580mm, Ø25.4mm, Sweep: 10°, H:15mm

Stem
Alloy, Ø25.4mm, E:60mm, H:41mm Rise: 15°

Saddle
Spyke custom design, steel rail

Seat Post
27.2mm x 250mm, Alloy

Seatpost Clamp
31.8mm, Alloy, QR

Pedals
9/16" Ball, PP

WEIGHT

Bike Weight
13.66kg

RIDER WEIGHT LIMIT

120kg - combined weight of bike and rider (including all kit).