



Saves Your Energy

PRODUCT CARD

1/6/17

KE69.3

Clampo Pro terminal

Code	KE69.3
GTIN	6418677192050
Name	Clampo Pro terminal Ensto Clampo Pro Tapping block, yellow/green, Al/Cu 35-240 mm ²
Description	Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm ² .
Vendor	Ensto Finland Oy



Technical specification

Dimensions

Weight:	0.44 kg
Conductor cross-section:	35-240

Temperatures

Operating temperature:	≤ 80 °C
------------------------	---------

Electrical values

Pollution degree:	3
-------------------	---

Materials

Housing:	Polyamide
----------	-----------

Colors

Color:	Yellow-green
--------	--------------

Features

Number of poles:	1
Screw head:	Hexagon
Screw head size:	8 mm
Number of termination points:	4
Mounting:	Screw

Mechanical

Tightening torque: 12 Nm (35-70mm²), 45 Nm (95-240mm²)

Certificates

Standards: EN 60947-7-2, IEC 61238-1, UL 1059

Connector class: A

UL category: XCFR2

UL File no.: E192532, E192532

Ratings

ETIM class: EC000897

US specific

Conductor size: 500-3/0

Tightening torque: 360 Lb-In

ETIM

ETIM

Colour: Green/yellow

Length: 130 mm

Mounting method: Direct mounting

Nominal rated voltage: 800 V

Connectable conductor cross section fine-strand without cable end sleeve: 35 ... 185 mm²

Connectable conductor cross section fine-strand with cable end sleeve: 35 ... 185 mm²

Connectable conductor cross section multi-wired: 35 ... 240 mm²

Type of electrical connection 1: Screw connection

Connection position: Sideways

Number of levels: 1

Number of clamp positions per level: 4

Material insulation body: Thermoplastic

Operation temperature: -5 ... 80 °C

Width/grid dimension: 64 mm

Height at lowest possible mounting height: 67 mm

Type of electrical connection 2: Screw connection

Inflammability class of insulation material acc. with UL94: V2

Packaging

Default package

Unit: PCS

Size: 1