

JOTAPROFF Primer

Product description

Type

Solvent free waterborne dispersion paint for use indoors in dry rooms.

Recommended use

Used as a primer on walls and ceilings made of plaster, concrete, putty, building boards, fiberglass strip/fiber cloth. Suitable for equalizing suction. Fills well and provides good adhesion, so that the top coat has a smooth and nice surface.



Product data

| | |
|--------------------------------------|--|
| Packaging size | 10 L |
| Tinting | Do not tint or mix with other products. |
| Colors | White |
| Gloss level | Silky matt |
| Generic type | PVA copolymer dispersion panit |
| Solids by volume | 38 ± 2 volume% |
| Specific gravity | 1.33 |
| VOC for Ready-for-Use Mixture | EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC. |

Application data

Remarks

Stir well before use.

Application equipment / methods

Roller, brush or spray. Apply rich and evenly.

Guiding data for airless spray

The choice of nozzle tip / spray angle / pressure must be adapted to the relevant spray equipment and surface.

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Spreading rate and film thickness

| | Spreading rate per coat (m ² /liter) | Film thickness per coat (µm) | |
|--------------|---|---------------------------------|------------------|
| | | Wet (calculated) | Dry (calculated) |
| Recommended: | 7 – 10 | 100 – 143 | 38 – 54 |

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Cleaning of spillage

JOTUN Spesial wipes are recommended to clean spillage. **JOTUN Spesial wipes** are a convenient washing/cleansing wipe for use before and during paint work.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

| | |
|------------------------|-------|
| Relative Humidity (RH) | 50 % |
| Air temperature | 73 °F |
| Substrate temperature | 73 °F |

| | |
|---------------------|--------|
| Surface (touch) dry | Ca 1 h |
| Recoatable, minimum | 2 h |

Directions for use

WORK PREPARATION

The substrate must be clean, sound and dry.
Clean if necessary with **JOTUN Spesialvask for maling**.

| | |
|-------------|---|
| Primer: | Apply one coat of this product. |
| Topcoating: | Use Jotun's recommended interior products. 2 coats. |

Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time).
If cleaning is necessary, the pH of the detergent must not exceed pH 9.
JOTUN Spesialvask for maling is recommended.
For daily cleaning the temperature of the wash water must be <40 °C.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Green Building Standards

Swan (2096 0002)

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

BREEAM® International (2021)/BREEAM® International (2016)

- The emission requirements for M1: Classification of Indoor Environment 2018
-
- Property criteria in BASTA (2016:A1)
- Accepted according to Building Evaluation Assessment Criteria (Byggvarubedømmningens Bedømningskriterier) 4.0 (2016)
- Class B according to Bedømningskriterier (Assessment Criteria) 6.0 for SundaHus (2013)

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

BREEAM® International v6.0 (2021)/BREEAM® International (2016)

- Hea 02: VOC exemplary emission (ISO 16000-series) and the VOC content for Interior matt walls and ceilings (Gloss <25@60°) (10 g/l).
- Mat 01: Product-specific Type III EPD (ISO 14025;21930, EN 15804+A2) for Jotun A/S.

BREEAM-NOR v6.0 (2022)

- Hea 02-02: Pattern valid level. VOC content for "Matt indoor wall and ceiling paint" (10 g/l) and emission requirements (ISO 16000 series).
- Mat 02: Product-specific Type III EPD (ISO 14025, ISO 21930, EN 15804+A2) for Jotun A/S.
- Mat 02: The product's safety data sheet confirms that the product does not contain any substances on the Norwegian priority list (A20 list) and REACH approval/authorisation list – Annex XIV, prohibitions and restrictions – Annex XVII and SVHC candidate list.

BREEAM® NOR (2016)

- Hea 02: VOC content for "Matt indoor wall and ceiling paint" (30 g/l) (EU Directive 2004/42/CE) and emission requirements (ISO 16000 series).
- Mat 01: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Jotun A/S.
- Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional certificates and approvals may be available on request.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Indoor environment / Emission

The product gives low emission which is measured on a neutral substrate. Substrate and preparation prior to treatment will have an influence on the total emission from finished surface.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

60648469

NOBB module number

60648466

Contact information

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Tel: 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.