

JOTUN Husvask

Product description

Type

Universal outdoor maintenance detergent.



Features and benefits

JOTUN Husvask is used for the annual maintenance washing of the house's cladding. If the house is to be stained or painted, it is recommended to use **JOTUN Kraftvask**. **JOTUN Husvask** is a highly foaming outdoor cleaner when applied with a foam cannon. **JOTUN Husvask** will not attack aluminium, steel, plastic, glass etc. when dilution or working time is as recommended. Be careful not to get the detergent on self cleaning windows as it may damage the cleaning layer of the glass. Effectively removes all kinds of dirt.

Recommended use

JOTUN Husvask is a special cleaning agent recommended for the annual cleaning of house exteriors and other outdoor areas.

Substrate

Painted or stained woodwork. Terraces, outdoor furniture, walls, roofs and courtyards.
Not to be used on boats, cars or caravans.



Product data

Packaging size	1 L and 4 L
Generic type	Synthetic detergent.
Specific gravity	1.07
pH value	11 diluted with water 1:10
Contents	1-10 % cationic surfactants 1-10 % non-ionic surfactants

Application data

Remarks

Avoid working in direct sunlight (will loose effect). Avoid treating large areas at a time. Walls should be kept wet at any time. Avoid spraying the product directly onto plants. Any spills may be rinsed off with clean water.

Warning!

Use gloves to avoid drying of the skin. Avoid contact with eyes. Use eye protection (e.g. protective goggles). In case of contact with the eyes, rinse thoroughly with large amounts of fresh water.

Application equipment / methods

Outdoors: Best result is achieved using a scrubbing brush. Airless Spray w / dosage or spray gun may also be used. Airless spray must be used with caution. The distance between nozzle and surface: Min. 30 cm. Pressures over 70 bar: The distance to the wall/substrate and the spray angle must be increased further. Intense stream or the use of "turbo nozzle" could destroy cladding surface in total, and should therefore be avoided.

The use of high pressure spray on cladding:

A high pressure cleaner may simplify the house cleaning, but it must be used correctly and with caution to avoid possible damages to the wood. In worst case the water may penetrate behind the cladding and into the wall, causing larger damages such as blistering/flaking and/or decay. In addition, the wood may be chipped and destroyed, and the paint film can be "blown off" the surface.

If there are cracks in the substrate, big gaps between boards, the ventilation behind the cladding is poor, or if other constructional weaknesses are observed, high pressure spray should not be employed. Avoid spraying upwards the cladding and in to cornice boxes, valves etc. Start washing the wall from below, keeping the spray in a downward angle or sideways, allowing the water to drain of the wall. Remember that it is primarily the detergent and the amount of water that shall remove dirt, not the pressure. Hosing down oil stained surface must be performed carefully.

Cleaning of painting tools

Water

Product mixing ratio (by volume)

1:10

Mixing ratio:

Mixing ratio when using a **low-pressure sprayer**: 1 liter JOTUN Husvask to 10 liters water.

Mixing conditions when using a **foam cannon**: The product must not be diluted with water. Adjust consumption using the foam cannon's adjustment screw.

Spreading rate and film thickness

Comments: 1 liter mixed liquid for approximately 15 m².

Directions for use

Outdoors: 1:10 with water for normal cleaning using a low-pressure sprayer. Apply to dry surface and leave 3-5 minutes to work. On vertical surfaces the detergent should be applied from below and upwards. Walls should be kept wet at any time.

If the surface is very dirty, additional use of tools like brushes etc. may be necessary during the cleaning process, or repeat the treatment.

Fungus or grass stained surfaces should be disinfected with a suitable anti fungal treatment after washing.

General: Use a facade wash brush mounted on an extension shaft for better efficiency and the cleanest result.

Application with foam cannon attached to a pressure washer.: The container is filled undiluted with Jotun House Wash. The mixing ratio and foam pattern are adjusted using the foam cannon's adjustment screw. In case of wind, ensure that the surrounding area is cleared of objects that should not be foamed.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright. Frost free storage because the container may burst during freezing.

Disposal of waste

Detergent must not be discharged into drains, but to a reception centre for dangerous waste.



Sorted as plastic when empty and dry.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Contact information

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Tel: 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.