

Plastic single-socket plugs and extensions - German standard



Pack	Cat.Nos	
		2P plugs and extensions - with extraction ring
	Gencod labelling	6 A
30	0 501 62	○ Plug - White
15	0 501 66	○ Extension - White
30	0 501 63	● Plug - Black
30	0 501 64	● Plug - Bronze
30	0 501 65	● Plug - Aluminium
		10 A
30	0 503 12	○ Plug - White
30	0 503 14	● Plug - Black
30	0 503 13	● Plug - Bronze
15	0 503 05	○ Extension - White
15	0 503 06	● Extension - Black
		2P plugs - 16 A - extra-slim
	Gencod labelling	Side outlet plugs, ideally behind an item of furniture
15	0 501 83	2 x 1.5 mm ² max. cable, screw cable grip
15	0 501 84	○ White
		● Black
		2P+E plugs - 16 A and extensions
	Bulk	Gencod labelling
25	0 503 15	0 501 87
25	0 503 16	0 501 88
15	0 503 17	0 501 89
25		0 501 77
25		0 501 78
15		0 501 79
		○ Straight outlet plug - White
		○ Side outlet plug - White
		○ Straight outlet extension - White
		● Straight outlet plug - Black
		● Side outlet plug - Black
		● Straight outlet extension - Black
		2P+E plugs - 16 A and extensions with rings
	Bulk	Gencod labelling
25	0 503 24	0 501 92
10	0 503 25	0 501 93
25	0 503 30	0 501 90
10	0 503 31	0 501 91
25	0 503 28	0 501 94
10	0 503 29	0 501 95
		3 x 2.5 mm ² max. cable, screw cable grip
		● Plug - Grey
		● Extension - Grey
		○ Plug - White
		○ Extension - White
		● Plug - Black
		● Extension - Black
	Sleeve	2P+E extension - 16 A - side outlet
4	0 501 99	○ White/Grey
		Removable accessory packaging enabling attachment
		2P+E plugs - 16 A - easy extraction
	Gencod labelling	System enabling extraction of sockets thanks to the lever-extractor
5	0 501 75	3 x 1.5 mm ² max. cable, screw cable grip, side outlet
5	0 501 76	○ White
		● Black and Grey
		2P+E plugs - 16 A - cable orientation
	Gencod labelling	3 x 0.5 mm ² max. cable, screw cable grip.
10	0 501 72	Enables the cable to be moved to 360°
10	0 501 73	○ White
		● Black and Grey

Single-socket plugs

British standard



Pack	Cat.Nos	British standard plugs
		With integrated fuse for protection against overloads
		○ White
20	0 503 26	 13 A - 250 V \sim - 2P+ \pm  ASTA certification
20	6 500 13	 13 A - 250 V \sim - 2P+ \pm
20	6 500 15	 15 A - 250 V \sim - 2P+ \pm