

VISITOR PREMIUM

Anti slip overshoe with safety cap



REF « VIP »

- Composition: Rubber and protective toe cap made of aluminium/titanium.
- Professional use: Slip resistance and toes protection. Secure moves in the work place.
- ✓ Outstanding grip coefficient
- ✓ Toe cap made of aluminium/titanium. Ultra light!
- ✓ Multidirectional straps : secure hold of the foot
- ✓ Only 4 sizes to cover from 34 to 47
- ✓ Color code to track sizes
- ✓ Can be adapted to most kind of footwear
- ✓ Reusable
- ✓ Tiger-grip® anti slip sole with self cleaning studs

Certifications

PPE REGULATION (EU) :
2016/425

(personal protective equipment)



EUROPEAN STANDARDS

CE Certification:
0075/1344/161/01/18/0113

- NF EN ISO 20345 / 2011
- NF EN 12568
- NF EN 13287
- Oil resistance (FO)



CE PPE CERTIFIED Risk II

Certified Organism:

CTC N° 0075/69367 Lyon - France



AMERICAN STANDARDS

Certification process ongoing

- NF EN 13287 – Anti slip properties

Certification SRC : SRA + SRB

SRB : Anti-slip coefficient on steel floors with glycerin

SRA : Anti-slip coefficient on ceramic floors with detergent

Surface	Contact with	Standard ISO 13287	VISITOR PREMIUM results
Steel	Oil	SRB = 0.18	+ 110 % = 0.38
Ceramic	Detergent	SRA = 0.32	+40% = 0.46

- NF EN 12568 – Toe Cap resistance:

200 joules resistance and resistant to crushing under max. Load of 1500 DaN

Physico-mechanical tests

Test	Standard	VISITOR PREMIUM results	Unit
Shock resistance	EN ISO 20344	20.5	mm
Crushing resistance	EN ISO 20344	26	mm
FO Resistance	EN ISO 20344	-0.1	%

Antistatism: The overshoe meets antistatic and ESD properties.

The shoe and overshoe combination must necessarily be tested by the user

Sizes



	S				M				L				XL			
EU Sizes	34	35	36	37	38	39	40	41	42	43	44	45	46	47		
UK Sizes	1	2	3	4	5	6	6.5	7	8	9	10	10.5	11	12		
US Woman	4	5	6	7	7.5	8	8.5	9	9.5	10						
US Man					5.5	6	7	8	8.5	9.5	10	11	11.5	12.5		

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

Storage and maintenance



- Hand washable - Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°C.

Design and manufacturing : TIGER-GRIP ENGINEERING



contact@tigergrip.com



120, rue Fornier
31700 BEAUZELLE, France



+ 33 5 34 60 56 56

www.tigergrip.com