

PRODUCT CARD



PRODUCT CODE: OR-AE-13614/2

EAN CODE: 5908254821035

MICRO cable connector, straight, IP68, 2x1.0mm², 450V/10A, 2 pcs.

MICRO cable connector, with a simple shape and very small dimensions. High degree of tightness IP68 protects against external factors, and the innovative O-Ring seal does not expose the seal to damaging external, chemical and mechanical conditions. The material used for the production of the connector is resistant to UV rays and is suitable for outdoor use. Its rigid, compact form and innovative sealing enable installation in the ground. The contacts are made of brass, additionally protected against oxidation with a layer of nickel. The cable gland is equipped with a thick gasket that tightly seals all inserted wires. The product is perfect for outdoor low-voltage lighting installations (with 2 wires + and -). The set includes two pieces.



Wire cross-section:

1,5mm²



UV radiation resistance:



Number of wires:

2



Case flammability standard

UL94:

V1



Current:

16A



Degree of protection (IP):

68



Pieces in the set:

2pcs

General information

Connector type: MICRO straight

Wire cross-section: 1,5 mm²

Number of wires: 2

Cable gauge: 2-6,5 mm

Power supply: 450V

Current: 16 A

Contacts material: nickel-plated brass

Flame-resistant casing: yes

UV radiation resistance: yes

Case flammability standard UL94: V1

Dimensions - length (mm): 57 mm

Degree of protection (IP): 68

Type of connection: screw clamp

Underground installation: yes

Material housing: PA6

Pieces in the set: 2 pcs

Diameter: 16 mm