

CODE: MBK07-060AF-P1E

ERP: 0501025

Fire Extinguisher 6Lt Foam Portable

Fire Extinguisher 6Lt Foam 1,5%, with one seam vessel with Internal Plastic Layer and Pressure Gauge Safety Release Valve.

Metallic bracket included

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	ASSURALIA, BENOR, ITALY, KKI, MED, MIRTEC, NCP - KIWA, NF, TSE, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Foam
Capacity	6Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	7,9 lt
Cylinder Height	470±5 mm
Cylinder Diameter	160±1,5 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	10,5 kg
Approx. Dimensions	630x200 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P¹ str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com