

JOTAPROFF CoverTech 03

Product description

Type

JOTAPROFF CoverTech 03 is a water-thinned paint with barrier properties for overpainting nicotine, soot and water damage.



Features and benefits

JOTAPROFF CoverTech 03 is used as a primer and topcoat, for both walls and ceilings with damage from nicotine, soot and water damage. Very good barrier properties. Nice, matt finish. For very dirty surfaces, three coats may be necessary.

Recommended use

Used for previously painted walls and ceilings of plaster and particleboard with damage from nicotine, soot and water damage.



Product data

Packaging size	10 L (filling level 9 L)
Base availability	9918 Klassisk hvit-base (S0500-N)
Tinting	If base as 9918 Klassisk Hvit is bought as white colour, it shall NOT be tinted using Jotun Multicolor . All other colour formulations to be mixed over Jotun Multicolor .
Colors	Can be tinted in selected colours using Jotun Multicolor .
Gloss level	03



Solids by volume	49 ± 2 volume%
Specific gravity	1.54
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/i): 140 g/l. The product contains max 20 g/l VOC.
Washability class	EN 13300:2022 washing class 1, ISO 11998:2006

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Preferred application with roller or airless spray. Apply rich and evenly.

Guiding data for airless spray

Nozzle tip 0.018–0.021"

The choice of nozzle tip / spray angle / pressure must be adapted to the relevant spray equipment and surface.

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Thinner

Shall not be thinned.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
	8 – 10	100 – 125	49 – 61

Conditions during application

Air and surface temperature must be above +10 °C during application.

Cleaning of spillage

JOTUN Spezial wipes are recommended to clean spillage. **JOTUN Spezial wipes** are a convenient washing/cleansing wipe for use before and during paint work.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation, film thickness and degree of penetration.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	73 °F
Substrate temperature	73 °F

Surface (touch) dry	1 hour
Recoatable, minimum	4 hours (Depending on the penetration.)
Dry to use	Ca 24 hours
Fully cured	4 weeks

Directions for use

Substrate	Treatment
Previously painted surfaces discolored by soot, nicotine and water damage:	Topcoat: 2-3 x JOTAPROFF CoverTech 03

Additional information

For panel and wood substrates, 1-2 coats of **JOTUN Kvist- og sperregrunning** and 2 coats of **LADY Supreme Finish** are recommended.

Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spesialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste



Empty and dry pails can be sorted together with plastic packaging.
The metal handle must be removed and be sorted with metallic packaging.
See the QR code for more information.



Must be empty and dry

Liquid paint and washing water with paint residues must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.

Environmental labelling



2096 0002



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

The product meets the requirements of the BREEAM® NOR for the VOC and the A20 list.

Green Building Standards

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

BREEAM-NOR v6.1 (2023) / BREEAM-NOR v6.0 (2022)

- Hea 02-02: Pattern valid level. VOC content for "One-component special paint" (100 g/l) and emission requirements (ISO 16000 series or CDPH v 1.2).
- Mat 02: Product-specific Type III EPD (ISO 14025, ISO 21930, EN 15804+A2) for Jotun A/S.
- Mat 02: The product's safety data sheet confirms that the product does not contain any substances on the Norwegian priority list (A20 list) and REACH approval/authorisation list – Annex XIV, prohibitions and restrictions – Annex XVII and SVHC candidate list.

BREEAM® NOR (2016)

- Hea 02: VOC content for "Interior matt walls and ceilings" (30 g/l) (EU Directive 2004/42/CE) and emission demands (ISO 16000-series).
- Mat 01: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Jotun A/S.
- Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional information: Certificates and approvals may be available on request.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

60776093

NOBB module number

60775620

Contact information

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Tel: 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Technical Data Sheet

JOTAPROFF CoverTech 03



This technical data sheet supersedes those previously issued.
The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product.
For your nearest local Jotun office, please visit our website at www.jotun.com.