

Data sheet

The Ultraflat 54 floor drain DN 50, enclWPM, Slotted grating



Article information

article number: 44750.20
 EAN code: 4026092080863
 Price group: 10

Product advantages

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section. Open seepage water opening, no flooding of the waterproofing level in the event of build-up.

General features

Nominal size (DN)	50
Outer diameter (OD)	50 mm
Odour trap	included
Sustainable	through the use of recycled material

Version

System	125
Seepage opening	optional
Waterproofing layer on the drain body	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including)	W2-I
Sealing water height	22 mm

Dimensions

Vertical adjustment	63 116 mm
Net weight	0.67 kg
Gross weight	0.67 kg
Type of height adjustability	vertically adjustable upper section
Length	246 mm
Width	200 mm
Height	54 mm
Packaging dimension: length	245.7 mm
Packaging dimension: width	200.6 mm
Packaging dimension: height	121.5 mm

Tank/drain body

Number of outlets	1
Material of drain body	ABS

Coverage features

Type of cover	Slotted cover
Cover material	Stainless steel 14301
Colour of cover	silver
Width of cover	120 mm
Height of cover	16 mm
Length of cover	120 mm
Min. flooring height	9 mm
Surface	Polished SST
Frame material	ABS
Locking	unlocked
Load class	K 3 (EN 1253-1)
Rim width	130 mm
Rim length	130 mm
Max. flooring height	62 mm
Shape of upper section	square
Upper section material	ABS