



CA12030L - Lærredstape -Byggeri

Description	Denne enkeltklæbende tape består af en vandtæt polyetenbelagt vævbærer og en naturgummiklæber.
Product properties	Tapen har en god holdbarhed imod vand og både høje og lave temperaturer. Tapen er smidig og fleksibel, med god vedhæftning og høj trækstyrke, men er stadigvæk let at rulle af samt at rive over i hånden.
Applications	En lærredstape af høj kvalitet fremstillet specielt til professionel anvendelse af f.eks. bygningsarbejdere og håndværkere. Den er egnet til de fleste praktiske formål på en byggeplads og andre krævende miljøer på grund af sin styrke og gode egenskaber. Let at rive over med fingrene. TUN Numre: Sølv:#5181125 / Sort: #
Storage and ageing	Opbevaring ved +20°C og 50% relativ fugtighed - og ikke i direkte sol.
Applying tips	Alle overflader skal være rengjorte og klar til montering. Afrensning foretages bedst med IPA (iso-propyl-alkohol) og en ren klud. Det anbefales at montere tapen over et fast underlag, og ved temperaturer der almindeligvis ikke er under +10 grader.

TECHNICAL DATA

Carrier	PE/cloth	
Adhesive	Rubber natural	
Colour	Black, Silver Grey, White	
Liner	None	
Thickness Total	0,255 mm	10 Mils
Adhesion on stainless steel	15 N/25mm	3,43 Lbs/inch
Tensile strength length	140 N/25mm	32 Lbs/inch
Elongation length	20 %	
Service temperature	Between -35 and 90 °C	Between -31 and 194 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Denmark A/S
Gydevang 40
3450 Allerød
tel +45 - 48 17 12 11
fax +45 - 48 17 40 52
www.stokvistapes.dk
info@stokvistapes.dk